



-NOTES-

- 1.Electrical:
 Contact resistance:50m ohms max.
 Dielectric withstanding voltage:
 250V RMS.
 Insulation resistance:
 50M ohms min.
- 2.Mechanical:
 MATE AND UNMATE FORCE:
 MATE FORCE:3.0kg MAX
 UNMATE FORCE:1.02kg MIN
 Durability:3000cycles MIN.
- 3.Environment:
 Operating Temperature:-20°to+85°.
- 4.FINISH:
 TERMINAL: GOLD Plated Over NICKEL
 Contact area,TIN ON
 SOLDER TAIL AREA.
 SHELL: SUS WITH TIN Plated:
- 5.COLOR:
 HOUSING: BLACK.

Contact Finish: 10: 10u"Gold

TOLERANCE:		UNIT				
X. ± 0.50	X.° ± 1°	MM				
.X ± 0.30	.X° ± 1°	SHEET				
.XX ± 0.20	.XX° ± 1.0°	1/1	DRAW:	Whm	2013.4.15	P/N: 5634-160522
.XXX ± 0.10			SCALE	DESIGN:		ITEM:
		1:1	CHECK:			Micro USB 5P B/F DIP 180
		REV: A	APPR:			DRW NO:



LTR	ECN NO	REVISION	RECORD	DRAW	DATE
1					