

# RIGHT ANGLE MICRO POWER CONNECTOR



## 5752 SERIE. Pitch 3.00 mm. (0.118"). High current / High density.

### Features

- Available in 2 to 12 circuits in single wire
- Insulation Material: PBT; UL 94V-0
- Contact Material: Brass, different plating opt. available
- Mates with 5750 series housing
- Positive lock
- Max. current rating: 5 A

### Dimensional Information

### Ordering and Dimensional Information

Circuits	Part Number	Dimensions		
		A	B	C
2	5752 - 2021	3.00 (.118)	9.00 (.354)	-
3	5752 - 2031	6.00 (.236)	12.00 (.472)	-
4	5752 - 2041	9.00 (.354)	15.00 (.591)	4.70 (0.185)
5	5752 - 2051	12.00 (.472)	18.00 (.709)	7.70 (0.303)
6	5752 - 2061	15.00 (.591)	21.00 (.827)	10.70 (0.421)
7	5752 - 2071	18.00 (.709)	24.00 (.945)	13.70 (0.539)
8	5752 - 2081	21.00 (.827)	27.00 (1.063)	16.70 (0.657)
9	5752 - 2091	24.00 (.945)	30.00 (1.181)	19.70 (0.776)
10	5752 - 2101	27.00 (1.063)	33.00 (1.299)	22.70 (0.894)
11	5752 - 2111	30.00 (1.181)	36.00 (1.417)	25.70 (1.012)
12	5752 - 2121	33.00 (1.299)	39.00 (1.535)	28.70 (1.130)

