

RIGHT ANGLE CONNECTOR SUB-D




8098-8099 SERIES. Right Angle . For PCB Solder.

Features


- Available in 9 and 25 circuits female and 9 male
- Insulator Material: Thermoplastic with fibre glass filled; UL 94V-0
- Contact Material: Phosphor Bronze, stamped
- Rear Part completely insulated
- Metal shell; Tin plated
- Available in different plating options
- The standard version includes: clip, grounding tap L2 and clinch nut 4-40 UNC
- For further options, please contact our Sales Department

Dimensional Information

FEMALE CONNECTOR



MALE CONNECTOR



Ordering and Dimensional Information

Female Connector

CIRCUITS	Part Number	DIMENSIONS			
		A	B	C	D
9	8098-T09C	16.30 (0.642)	25.00 (0.984)	30.80 (1.212)	6.95 (0.273)
25	8098-T25C	38.30 (1.507)	47.10 (1.854)	53.10 (2.090)	6.93 (0.272)

Male Connector

CIRCUITS	Part Number	DIMENSIONS			
		A	B	C	D
9	8099-T09C	19.92 (0.784)	25.00 (0.984)	30.80 (1.212)	6.95 (0.273)

T = Platings of the Pins

- T = 3. Gold flash over 1.27 μ Ni.
- T = 4. 0.25 μ Gold over 1.27 μ Ni.
- T = 5. 0.50 μ Gold over 1.27 μ Ni.
- T = 6. 0.75 μ Gold over 1.27 μ Ni.

C = Connector options

- C = 1. Standard version with grounding tap L2 and clinch nut 4-40 UNC mounted
- C = 0. Standard version with grounding tap L2 Inserted nut 4.40 UNC w/o hexagonal nut

