

SINGLE ROW VERTICAL PIN HEADER



8392 SERIES. 2.54 mm. (0.100") pitch. Machined contact.


General Features

- Available in 2 through 40 circuits
- 0.64 round pin in contact area
- With different plating options

Materials

- Insulator: PPS black + 30% GF UL 94 V-0
- Contact: Brass
- Operating temperature. -40°C to +105°C
- RoHS compliant

Dimension Information



MECANIZADO RECOMENDADO
(Tolerancia ±0.05)




Electrical Features

- Voltage rating: < 250V
- Current rating: < 3 A
- Contact resistance: < 10 mΩ
- Dielectric withstanding Voltage: 1000 V AC/minute
- Insulation resistance: >1000 MΩ

Mechanical Features

- Pin retention force to insulator: > 0.80 Kgf
- Durability: 500 Cycles



Ordering Information:

8392 - T- XX- 1
1 2 3 4

1. Connector Series

2. (T) Contact Plating

- T = 3. gold flash over 30-50μ" Ni overall
Recommended Finish
- T = 15. 15μ" selec. gold over 30-50μ" Ni overall
- T = 16. 30μ" selec. gold over 30-50μ" Ni overall

3. (XX) Number of circuits

- Available in 2 through 40 circuits

Dimensions: (In mm.)

A = 2.54 x (XX*-1)

B = 2.54 x (XX*)+0.41

* XX (Number of circuits)