

CABLE TO CABLE RJ45 IP 67



3165 SERIES. Cable to cable RJ45 IP67.


General Features

- Available in 8/8 circuits
- Accept standard plugs FCC-68
- 50 U Selective gold plating in contact area
- IP67 waterproof connector
- Coupler Jack-Jack inside. It can fix on a panel

Materials

- Insulator: Thermoplastic UL 94V-0
- Contact: 0.40 mm thickness phosphor bronze
- Receptacle housing: Thermoplastic UL 94V-0
- Panel nut: Thermoplastic UL94V-0. Panel Gasket: Silicone
- Operating temperature. -25°C to + 85°C
- RoHS compliant

Dimension Information



Electrical Features

- Voltage rating: < 125V
- Current rating: < 1.50 A
- Contact resistance: < 20 mΩ
- Dielectric withstanding Voltage: 300 V AC/minute
- Insulation resistance: >1000 MΩ

Mechanical Features


- Durability: 1500 Cycles

Ordering Information:

3165 - T- 88- 1

T = Plating Options

- T = 2. Tin-plated
- T = 3. Gold flash over nickel
- T = 4. 10μ" gold over nickel
- T = 5. 15μ" gold over nickel
- T = 6. 30μ" gold over nickel



RECOMMENDED CUT OUT

ASSEMBLY :

